


## PMV0603-5R0E0R2


### Features

- Operating voltage: 5 Vdc
- Fast response, instantly clamping the transient over voltage.
- High surge current handling capability.
- High energy absorption capability.
- Low clamping voltages, providing better surge protection.
- Low capacitance values, providing digital switching circuitry protection.
- High insulation resistance, preventing electric arcing to the adjacent devices or circuits.
- Meet IEC 61000-4-2 level 4 standard.



### Applications

- Universal Serial Bus (USB).
- Mobile communication.
- Computer/DSP product.
- Video and audio ports.
- Portable/Hand-Held Products.
- Data, Diagnostic I/O ports.



### General Characteristics Definition


- Operating temperature: -55 ~ 125°C
- Storage temperature: -55 ~ 125°C

### Material


- Electrode: Ag/Ni/Sn
- Chip body: Zinc oxide

### Part Number Code


#### PMV 0603 - 5R0 E 0R2



### Physical Dimensions



#### Solder pad layout



Symbol	Dimension (mm)
L	1.6±0.2
W	0.8±0.2
D	0.9 max.
E	0.35±0.1
A	2.6 typ.
B	0.8 typ.
C	0.9 typ.

#### Note:


1. All dimensions are in millimeters.
2. No marking on the device.

## PMV0603-5R0E0R2

### Electrical Characteristics

Part Number	Max Allowable Voltage		Varistor Voltage $V_b @ 1 \text{ mA}$		Withstand Surge Current $I_{PP}$ 8/20 $\mu\text{s}$	Max Clamping Voltage $V_C$		Capacitance @ 1MHz		
	$V_{RMS}$ (V)	$V_{DC}$ (V)	Min (V)	Max (V)		V (V)	I (A)	Min (pF)	Typ (pF)	Max (pF)
	PMV0603-5R0E0R2	-	5	120	160	1	50	1	0.1	0.2


### Peak Pulse Current Test Waveform



$O_1$  = Virtual Origin of Wave  
 $T$  = Time from 10% to 90% of Peak  
 $T_1$  = Rise Time =  $1.25 \times T$   
 $T_2$  = Decay Time


**Example** - For an 8/20 ms current waveform  
 $8 \mu\text{s} = T_1 = \text{Rise Time}$   
 $20 \mu\text{s} = T_2 = \text{Decay Time}$

### Power Derating Curve



### Lead Free Reflow Soldering Recommendations

<b>Preheat</b>	
- Temperature Min ( $T_{s\_min}$ )	150°C
- Temperature Max ( $T_{s\_max}$ )	200°C
- Time ( $T_{s\_min}$ to $T_{s\_max}$ )	60-180 seconds
- Average Ramp-Up Rate	1~3°C/second
<b>Peak Temperature</b>	260°C max.
<b>Time within 5°C of actual Peak Temperature (<math>t_p</math>)</b>	40 seconds max.
<b>Ramp-Down Rate</b>	6 °C /second max.



**Note:** If the wave soldering temperatures exceed the recommended profile, devices may not meet the performance requirements.


## PMV0603-5R0E0R2

### Reliability Test

Environmental Ratings										
Test Parameter	Test Condition / Description	Performance Requirements								
Dry Heat Loading	The specimen shall be applied continuously the maximum allowable voltage at the specified conditions for specified period and then stored at room temperature and normal humidity over 2 hours. Thereafter, the change of $V_b$ and mechanical damage shall be examined. Ambient temp: $85\pm 2^\circ\text{C}$ / Period: $1000\pm 24$ hours	$\Delta V_b/V_b \leq 10\%$								
High Temp Storage	In a dry oven without load. Ambient temp: $125\pm 2^\circ\text{C}$ / Period: $1000\pm 24$ hours	$\Delta V_b/V_b \leq 10\%$								
Damp Heat/ Humidity Loading	The specimen shall be applied continuously the maximum allowable voltage at the specified conditions for specified period and then stored at room temperature and normal humidity over 2 hours. Thereafter, the change of $V_b$ and mechanical damage shall be examined. Ambient temp: $40\pm 2^\circ\text{C}$ , 90~95%RH / Period: $1000\pm 24$ hours	$\Delta V_b/V_b \leq 10\%$								
Temperature Cycle	Condition the specimen to each temperature from step 1 to step 4 in this order for the period shown in the table of specifications. The change of $V_b$ and mechanical damage shall be examined after 2 hours. <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">Step 1</td> <td style="text-align: center;"><math>-40\pm 3^\circ\text{C}</math> / 30min.</td> </tr> <tr> <td style="text-align: center;">Step 2</td> <td style="text-align: center;">Room temp / 15min.</td> </tr> <tr> <td style="text-align: center;">Step 3</td> <td style="text-align: center;"><math>85\pm 2^\circ\text{C}</math> / 30min.</td> </tr> <tr> <td style="text-align: center;">Step 4</td> <td style="text-align: center;">Room temp / 15min.</td> </tr> </table>	Step 1	$-40\pm 3^\circ\text{C}$ / 30min.	Step 2	Room temp / 15min.	Step 3	$85\pm 2^\circ\text{C}$ / 30min.	Step 4	Room temp / 15min.	No Visible damage $\Delta V_b/V_b \leq 10\%$
Step 1	$-40\pm 3^\circ\text{C}$ / 30min.									
Step 2	Room temp / 15min.									
Step 3	$85\pm 2^\circ\text{C}$ / 30min.									
Step 4	Room temp / 15min.									
Low Temp Storage	In a cooling chamber without load. Ambient temp: $-40\pm 2^\circ\text{C}$ / Period: $1000\pm 24$ hours	$\Delta V_b/V_b \leq 10\%$								

### Packaging Information

Part Number	Quantity (EA/Roll)	Reel Dimension (mm)	
		Diameter	Thickness
PMV0603-5R0E0R2	4000	$178.0\pm 1.0$ (7" Paper Reel)	$9.0\pm 0.5$



Symbol	Dimension (mm)
P	$4.0\pm 0.1$
P0	$4.0\pm 0.1$
D	$1.55\pm 0.05$
E	$1.75\pm 0.1$
F	$3.5\pm 0.1$
W	$8.0\pm 0.2$
T	$0.22\pm 0.05$
K	$1.2\pm 0.1$