


PT3621NT – ESD Protection Diode

Feature

- 280 Watts peak pulse power (8/20 μ s)
- Bidirectional configurations
- Solid state silicon-avalanche technology
- Low clamping voltage
- Low leakage current
- Protection one data line
- IEC61000-4-2 (ESD) ± 15 kV (Air), ± 8 kV (Contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)
- IEC61000-4-5 (Lightning): 5A (8/20 μ s)




Applications

- Power lines
- Personal Digital Assistants (PDA's)
- Notebooks, Desktops and Servers

Mechanical Data

- DFN1006 package
- Molding compound flammability rating: UL94 V-0
- Tape and Reel Packaging
- RoHS/WEEE Compliant

Schematic and PIN Configuration



DFN1006

Maximum Rating

Parameter	Symbol	Limit	Unit
IEC61000-4-2 ESD Voltage – Air Mode	$V_{ESD}^{(1)}$	± 15	kV
IEC61000-4-2 ESD Voltage – Contact Mode		± 8	
Peak Pulse Power	$P_{PP}^{(2)}$	280	W
Peak Pulse Current	$I_{PP}^{(2)}$	4	A
Maximum Lead Solder Temperature (10 seconds duration)	T_L	260	$^{\circ}$ C
Junction Temperature	T_J	-55~125	$^{\circ}$ C
Storage Temperature Range	T_{stg}	-55~125	$^{\circ}$ C

Note:

1. Device stressed with ten non-repetitive ESD pulses.
2. Non-repetitive current pulse 8/20 μ s exponential decay waveform according to IEC61000-4-5.
3. All ratings are measured at environmental temperature of $T_A = 25^{\circ}$ C unless otherwise noted.

PT3621NT – ESD Protection Diode

Electrical Characteristics


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Stand-off Voltage	$V_{RWM}^{(1)}$				36	V
Reverse Breakdown Voltage	V_{BR}	$I_T = 1\text{mA}$	40			V
Reverse Leakage Current	I_R	$V_{RWM} = 36\text{V}$		0.1	0.5	μA
Peak Pulse Current	I_{PP}				4.0	A
Clamping Voltage	$V_C^{(2)}$	$I_{PP} = 4\text{A}$			70	V
Junction Capacitance	C_J	$V_R = 0\text{V}, f = 1\text{MHz}$		25	30	pF

Note:

1. Other voltages available upon request.
2. Non-repetitive current pulse 8/20 μs exponential decay waveform according to IEC61000-4-5.
3. All ratings are measured at environmental temperature of $T_A = 25^\circ\text{C}$ unless otherwise noted.

Electrical Parameters

Symbol	Parameter
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_R	Reverse Leakage Current @ V_{RWM}
V_{RWM}	Reverse Stand-off Voltage



PT3621NT – ESD Protection Diode

Typical Characteristics

Fig.1 Peak Pulse Power Rating Curve




Fig.2 Pulse Derating Curve




Fig.3 Pulse Waveform-8/20 μs




Fig.4 Pulse Waveform-ESD(IEC61000-4-2)




Fig.5 IEC61000-4-2 +8kV Contact Discharge






Fig.6 IEC61000-4-2 -8kV Contact Discharge



PT3621NT – ESD Protection Diode

DFN1006 Package Outline Dimensions



Symbol	Dimensions (mm)		
	Min	Typ	Max
A	0.45	0.50	0.55
A1	0.00	0.02	0.05
b	0.45	0.50	0.55
c	0.12	0.15	0.18
D	0.95	1.00	1.05
e	0.65 BSC		
E	0.55	0.60	0.65
L	0.20	0.25	0.30
L1	0.05 REF		
h	0.07	0.12	0.17

Marking



Packaging Information

Order Code	Packaging	Reel Size	PCS/Reel
PT3621NT	DFN1006	7 inch	10,000